

Grand Canyon Gas Logs Vented Burner Specifications Sheet

2 & 3 Burner Specifications Chart (Indoor/Outdoor)								
Burner Size	Min. Fireplace Dimensions				BTU Ratings			
	Width		Depth	Height	2 Burner		3 Burner	
	Front	Rear			NAT.	L.P.	NAT.	L.P.
18"	30"	18"	12"	14"	52K	49K	46K	41K
21"	33"	21"	12"	14"	60K	60K	65K	60K
24"	36"	24"	12"	14"	64K	64K	74K	66K
30"	42"	30"	14"	14"	76K	79K	102K	91K
36"	48"	39"	14"	14"	81K	83K	111K	106K
42"	54"	45"	14"	14"	86K	87K	120K	121K

Jumbo / Jumbo Slimline Specifications Chart (Indoor/Outdoor)							
Burner Size	Min. Fireplace Dimensions					BTU	
	Width		Depth		Height	NAT.	L.P.
	Front	Rear	Jumbo	Slimline			
24"	36"	24"	-	21"	24"	75K	70K
30"	42"	30"	-	21"	24"	110K	105K
36"	48"	36"	23"	21"	24"	150K	145K
42"	54"	42"	23"	21"	24"	165K	160K
48"	60"	48"	23"	21"	24"	195K	190K
60"	72"	60"	23"	21"	24"	230K	225K

Kiva Burner Specifications Chart						
Burner Size	Min. Fireplace Dimensions				BTU	
	Width		Depth	Height	NAT.	L.P.
	Front	Rear				
18"	20"	18"	12"	14"	40K	35K
24"	25"	23"	12"	14"	52K	49K
30"	30"	28"	14"	14"	64K	64K

Glass Burner Specifications Chart (Indoor/Outdoor) (H&T Styles)						
Burner Size	Min. Fireplace Dimensions				BTU	
	Width		Depth	Height	NAT.	L.P.
	Front	Rear				
18"	30"	18"	12"	14"	52K	49K
24"	36"	24"	12"	14"	64K	66K
30"	42"	30"	14"	14"	76K	79K
36"	48"	36"	14"	14"	81K	83K
42"	54"	42"	14"	14"	90K	85K
48"	60"	48"	14"	14"	100K	95K
60"	72"	60"	14"	14"	110K	100K
72"	84"	72"	14"	14"	130K	105K

2 & 3 Burner See Through Specifications Chart (Indoor/Outdoor)								
Burner Size	Min. Fireplace Dimensions				BTU			
	Width		Depth	Height	2 Burner		3 Burner	
	Front	Rear			NAT.	L.P.	NAT.	L.P.
18"	21"	21"	18"	14"	103K	93K	103K	93K
21"	24"	24"	18"	14"	106K	93K	106K	93K
24"	30"	30"	18"	14"	118K	100K	118K	100K
30"	36"	36"	18"	14"	128K	115K	128K	115K
36"	42"	42"	18"	14"	135K	125K	135K	125K
42"	48"	48"	18"	14"	140K	130K	140K	130K

Jumbo See Through Specifications Chart (Indoor/Outdoor)						
Burner Size	Min. Fireplace Dimensions				BTU	
	Width		Depth	Height	NAT.	L.P.
	Front	Rear				
36"	48"	48"	26"	30"	165K	155K
42"	54"	54"	26"	30"	185K	170K
48"	60"	60"	26"	30"	210K	195K
60"	72"	72"	26"	30"	250K	235K