

# Owner's Manual

## Operation and Maintenance

**CAUTION! Risk of Fire! DO NOT** store instruction manuals inside fireplace cavity. High temperatures could cause a fire.

**INSTALLER:** Leave this manual with the appliance, not inside the appliance.

**CONSUMER:** Retain this manual for future reference. Do not store inside the appliance. Contact your dealer with questions regarding installation, operation or service.

**NOTICE: DO NOT** discard this manual!

### QUARTZ SERIES

#### Models:

QUARTZ32IFTN

QUARTZ32IFTL

QUARTZ36IFTN


QUARTZ36IFTL

QUARTZ42IFTN

QUARTZ42IFTL



GAS-FIRED



This appliance may be installed as an OEM installation in manufactured home (USA only) or mobile home and must be installed in accordance with the manufacturer's instructions and the *Manufactured Home Construction and Safety Standard, Title 24 CFR, Part 3280* in the United States, or the *Standard for Installation in Mobile Homes, CAN/CSA Z240 MH Series*, in Canada.

This appliance is only for use with the type(s) of gas indicated on the rating plate. This appliance is not convertible for use with other gases, unless a certified kit is used.

#### ▲ WARNING:

##### FIRE OR EXPLOSION HAZARD

Failure to follow safety warnings exactly could result in serious injury, death, or property damage.

- **DO NOT** store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance.
- **What to do if you smell gas**
  - **DO NOT** try to light any appliance.
  - **DO NOT** touch any electrical switch. **DO NOT** use any phone in your building.
  - Leave the building immediately.
  - Immediately call your gas supplier from a neighbor's phone. Follow the gas supplier's instructions.
  - If you cannot reach your gas supplier, call the fire department.
- Installation and service must be performed by a qualified installer, service agency, or the gas supplier.



**HOT GLASS WILL  
CAUSE BURNS.**

**DO NOT TOUCH GLASS  
UNTIL COOLED.**

**NEVER ALLOW CHILDREN  
TO TOUCH GLASS.**

A barrier designed to reduce the risk of burns from the hot viewing glass is provided with this appliance and must be installed for the protection of children and other at-risk individuals.

Decorative barrier front provided with this appliance.

Pour demander un exemplaire en français de ce Manuel du propriétaire, visitez [www.majesticproducts.com](http://www.majesticproducts.com).

# 1 Welcome

Read this manual before operating this appliance.  
Please retain this Owner's Manual for future reference.

Read the Installation Manual before making any installation or finishing changes.

## A. Congratulations

Congratulations on selecting a Majestic gas fireplace, an elegant and clean alternative to wood burning fireplaces. The Majestic gas fireplace you have selected is designed to provide the utmost in safety, reliability, and efficiency.

As the owner of a new fireplace, you'll want to read and carefully follow all of the instructions contained in this owner's manual. Pay special attention to all cautions and warnings.

This owner's manual should be retained for future reference. We suggest that you keep it with your other important documents and product manuals.

The information contained in this owner's manual, unless noted otherwise, applies to all models and gas control systems.

Your new Majestic gas fireplace will give you years of durable use and trouble-free enjoyment. Welcome to the Majestic family of fireplace products!

### Local Dealer Information

**DEALER:** Fill in your name, address, phone and email information here and appliance information below.

Dealer Name: \_\_\_\_\_  
Address: \_\_\_\_\_  
Phone: \_\_\_\_\_  
Email: \_\_\_\_\_

### Appliance Information:

Brand: \_\_\_\_\_ Model Name: \_\_\_\_\_  
Serial Number: \_\_\_\_\_ Date Installed: \_\_\_\_\_

## Listing Label Information/Location

The model information regarding your specific fireplace can be found on the rating plate usually located in the control area of the fireplace.

Type of Gas

Gas and Electric Information

**Majestic**, a brand of Hearth & Home Technologies  
7571 215th Street West, Lakeville, MN 55044

Energy Verified  
Rendement  
Énergétique Vérifié

**GAS-FIRED**  
**UL** LISTED

Vented gas fireplace heater - Not for use with solid fuel.  
Appareil de chauffage de foyer avec conduit d'évacuation des gaz  
- n'utilisez pas avec des combustibles solides. **ANSI XX.XX-XXXX** · **CSA X.XX-XXXX**

Type of Gas (Sorte De Gaz): **NATURAL GAS** CAN/CSA-P.X.X-XX · FE: %

This appliance must be installed in accordance with local codes, if any, or with the National Fuel Gas Code, ANSI Z223.1/NFPA 54, or the National Gas and Propane Installation Code, CSA B149.1, or with the Manufacturer's Installation and Safety Standard, Title 24 CFR, Part 3280 in the United States; or when such a standard is not applicable, the Standard for Manufactured Home Installations Standard, ANSI/NCSCS A225.1/NFPA 501A. Pour une installation dans une maison préfabriquée (E.U.S. seulement) ou dans une maison mobile du constructeur OEM: Ce poêle doit être installé en conformité avec la norme visant les maisons préfabriquées, CAN/CSA Z240MH, au Canada; ou avec la Manufactured Home Construction and Safety Standard, Title 24 CFR, Part 3280, aux États-Unis; ou, si une telle norme n'est pas applicable, la "Standard for Manufactured Home Installations, ANSI/NCSCS A225.1/NFPA 501A".

Minimum Permissible Gas Supply for Purposes of Input Adjustment.  
Approved Minimum (De Gaz) acceptable ..... x.x in. w.c. (Po. Col. d'eau)  
Maximum Pressure (Pression) ..... xx.x in. w.c. (Po. Col. D'eau)  
Maximum Manifold Pressure (Pression) ..... x.x in. w.c. (Po. Col. d'eau)  
Minimum Manifold Pressure (Pression) ..... x.x in. w.c. (Po. Col. d'eau)  
Minimum rate with variable regulator on control valve  
Total Electrical Requirements: 120Vac, 60Hz., less than 12 Amperes

**MADE IN USA**

**QR CODE** For use only with barrier(s): N'utiliser qu'avec la (les) barrière(s):  
Follow installation instructions. Suivre les instructions d'installation.

**QR CODE**

INSTALLATION MANUAL  
USA  
CANADA  
ALTITUDE: ..... 0-2000 FT. .... 0-4500 FT.  
MAX. INPUT BTU/h ..... xx,xxx ..... xx,xxx  
MIN. INPUT BTU/h ..... xx,xxx ..... xx,xxx  
ORIFICE SIZE ..... #xx DMS ..... #xx DMS

**Model:**  
(Modèle): XXXXXXXX

**Serial:**  
(Série):

Model Number  
Serial Number

Xxxx-xxx

## ▲ Safety Alert Key:

- **DANGER!** Indicates a hazardous situation which, if not avoided will result in death or serious injury.
- **WARNING!** Indicates a hazardous situation which, if not avoided could result in death or serious injury.
- **CAUTION!** Indicates a hazardous situation which, if not avoided, could result in minor or moderate injury.
- **NOTICE:** Used to address practices not related to personal injury.

**Note:** The term “recommend” or “recommended” does not indicate a requirement. It is a best practice suggested by Hearth & Home Technologies®.

## Table of Contents

### 1 Welcome

|                                         |   |
|-----------------------------------------|---|
| A. Congratulations . . . . .            | 2 |
| ➔ B. Limited Lifetime Warranty. . . . . | 4 |

### 2 Product Specific Information

|                                      |   |
|--------------------------------------|---|
| A. Appliance Certification . . . . . | 6 |
| B. Glass Specifications . . . . .    | 6 |
| C. BTU Specifications . . . . .      | 6 |

### 3 Important Safety and Operating Information

|                                                                               |    |
|-------------------------------------------------------------------------------|----|
| A. Appliance Safety . . . . .                                                 | 7  |
| B. General Operating Parts . . . . .                                          | 8  |
| C. Fuel Specifications . . . . .                                              | 8  |
| D. Wall and Mantel Temperatures . . . . .                                     | 8  |
| E. Good Faith Wall Surface/TV Guidelines . . . . .                            | 8  |
| F. Before Lighting Appliance. . . . .                                         | 10 |
| G. Lighting Instructions (IPI) . . . . .                                      | 11 |
| H. Appliance Break-In. . . . .                                                | 12 |
| I. Heat Management . . . . .                                                  | 12 |
| J. Operation During A Power Outage - IntelliFire Touch® . . .                 | 13 |
| K. Detailed Component Operating Instructions<br>- IntelliFire Touch . . . . . | 14 |

### 4 Maintenance and Service

|                                                               |    |
|---------------------------------------------------------------|----|
| A. Maintenance: Frequency and Tasks . . . . .                 | 16 |
| B. Maintenance Tasks - Homeowner . . . . .                    | 16 |
| C. Maintenance Tasks - Qualified Service Technician . . . . . | 18 |

### 5 Frequently Asked Questions and Troubleshooting

|                                                                                              |    |
|----------------------------------------------------------------------------------------------|----|
| A. Frequently Asked Questions - Appliance . . . . .                                          | 20 |
| B. Frequently Asked Questions - IntelliFire Touch<br>Controls (Optional IFT-RC400) . . . . . | 21 |
| C. Troubleshooting . . . . .                                                                 | 22 |

### 6 Reference Materials

|                                  |    |
|----------------------------------|----|
| A. Accessories . . . . .         | 24 |
| B. Service Parts . . . . .       | 25 |
| C. Contact Information . . . . . | 30 |

➔ = Contains updated information.

## → B. Limited Lifetime Warranty

### Hearth & Home Technologies LLC LIMITED LIFETIME WARRANTY

Hearth & Home Technologies LLC (“HHT”) extends the following warranty for HHT gas, wood, pellet and electric hearth appliances (each a “Product” and collectively, the “Product(s)”) and certain component parts set forth in the table below (“Component Part(s)”) that are purchased from a HHT authorized dealer or distributor.

#### **WARRANTY COVERAGE:**

HHT warrants that the Products and their Component Parts will be free from defects in materials and workmanship for the applicable period of Warranty coverage set forth in the table below (“Warranty Period”). If a Product or Component Parts are found to be defective in materials or workmanship during the applicable Warranty Period, HHT will, at its option, repair the applicable Component Part(s), replace the applicable Component Part(s), or refund the purchase price of the applicable Product(s). The maximum amount recoverable under this Warranty is limited to the purchase price of the Product. This Warranty is transferable from the original purchaser to subsequent owners, but the Warranty Period will not be extended in duration or expanded in coverage for any such transfer. This Warranty is subject to conditions, exclusions, and limitations as described below.

#### **WARRANTY PERIOD:**

Warranty coverage begins at the date of installation. In the case of new home constructions, Warranty coverage begins on the date of first occupancy of the dwelling or six months after the sale of the Product(s) by an independent, authorized HHT dealer or distributor, whichever occurs earlier. However, the Warranty coverage shall commence no later than 24 months following the date of Product shipment from HHT, regardless of the installation or occupancy date.

The term “Lifetime” in the table below is defined as: 20 years from the beginning date of warranty coverage for gas appliances, 10 years from the beginning date of warranty coverage for wood and pellet appliances, and 5 years from the beginning of warranty coverage for standalone gas log sets. These time periods reflect the minimum expected useful lives of the designated Component Parts under normal operating conditions.

| Warranty Period  |         | HHT Manufactured Appliances and Venting |        |      |          |         |                                                                                                                                                                             |
|------------------|---------|-----------------------------------------|--------|------|----------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Component Parts  | Labor   | Gas                                     | Pellet | Wood | Electric | Venting | Component Parts Covered by this Warranty                                                                                                                                    |
| 1 Year           |         | X                                       | X      | X    |          | X       | All parts including handles, external enameled components and other material except as covered by Warranty Conditions, Warranty Exclusions, and Warranty Limitations listed |
| 2 Years          |         |                                         |        |      | X        |         | All parts except as covered by Warranty Conditions, Warranty Exclusions, and Warranty Limitations listed                                                                    |
| 2 years          |         |                                         | X      | X    |          |         | Igniters, Auger Motors, Electronic Components, and Glass                                                                                                                    |
|                  |         | X                                       |        |      |          |         | Electrical components limited to modules, remotes/wall switches, valves, pilots, blowers, junction boxes, wire harnesses, transformers and lights (excluding light bulbs)   |
|                  |         | X                                       |        | X    |          |         | Molded Refractory Panels, Glass Liners                                                                                                                                      |
| 3 years          |         |                                         | X      |      |          |         | Firepots, burnpots, mechanical feeders/auger assemblies                                                                                                                     |
| 5 years          |         | X                                       |        |      |          |         | Burners and logs for standalone gas log sets (Vented and Vent Free gas log sets not sold as components of the fireplace or stove)                                           |
| 5 years          | 1 year  | X                                       |        |      |          |         | Vent Free Burners and Vent Free Log components of HHT manufactured fireplaces or stoves                                                                                     |
|                  |         |                                         | X      | X    |          |         | Castings, Medallions and Baffles                                                                                                                                            |
| 6 years          | 3 years |                                         |        | X    |          |         | Catalysts                                                                                                                                                                   |
| 7 years          | 3 years |                                         | X      | X    |          |         | Manifold tubes, HHT Chimney and Terminations                                                                                                                                |
| 10 years         | 1 year  | X                                       |        |      |          |         | Burners, logs and refractory components of HHT manufactured fireplaces or stoves                                                                                            |
| Limited Lifetime | 3 years | X                                       | X      | X    |          |         | Firebox and heat exchanger, FlexBurn® System (engine, inner cover, access cover and fireback)                                                                               |
| 1 Year           | None    | X                                       | X      | X    | X        | X       | All purchased replacement parts                                                                                                                                             |

## → B. Limited Lifetime Warranty (*continued*)

### **WARRANTY CONDITIONS:**

- Because HHT cannot control the quality of any Products sold by unauthorized sellers, this Warranty only covers Products that are purchased through an HHT authorized dealer or distributor unless otherwise prohibited by law; a list of HHT authorized dealers is available on the HHT branded websites.
- This Warranty is only valid while the applicable Product remains at the site of original installation.
- This Warranty is only valid in the country in which the HHT authorized dealer or distributor that sold the applicable Product is authorized to sell applicable Product.
- Contact your installing distributor or dealer for Warranty service. If the installing dealer or distributor is unable to provide necessary parts, contact the nearest HHT authorized dealer or supplier. Additional service fees may apply if you are seeking Warranty service from a dealer other than the dealer from whom you originally purchased the applicable Product.
- No HHT consumer should bear cost of warranty service or costs incurred while servicing warranty claims (i.e., travel, gas, or mileage) when the service is performed within the terms of this Warranty. Check with your dealer or distributor in advance for any costs to you when arranging a warranty call. Travel and shipping charges for parts are not covered by this Warranty.

### **WARRANTY EXCLUSIONS:**

This Warranty does not cover the following:

- Changes in surface finishes as a result of normal use. As a heating appliance, some changes in color of interior and exterior surface finishes may occur. This is not a flaw and is not covered under the Warranty.
- Damage to printed, plated, or enameled surfaces caused by fingerprints, accidents, misuse, scratches, melted items or other external sources and residues left on the plated surfaces from the use of abrasive cleaners or polishes.
- Repair or replacement of parts that are subject to normal wear and tear during the Warranty Period are not covered. These parts include: paint, wood and pellet gaskets, firebricks, grates, flame guides, batteries and the discoloration of glass.
- Minor expansion, contraction, or movement of certain parts causing noise. These conditions are normal and complaints related to this noise are not covered by this Warranty.
- Damages resulting from: (1) failure to install, operate, or maintain the applicable Product in accordance with the installation instructions, operating instructions, and listing agent identification label furnished with the applicable Product; (2) failure to install the applicable Product in accordance with local building codes; (3) shipping or improper handling; (4) improper operation, abuse, misuse, continued operation with damaged, corroded or failed components, accident, or improperly/incorrectly performed repairs; (5) environmental conditions, inadequate ventilation, negative pressure, or drafting caused by tightly sealed constructions, insufficient make-up air supply, or handling devices such as exhaust fans or forced air furnaces or other such causes; (6) use of fuels other than those specified in the operation instructions; (7) installation or use of components not supplied with the applicable Product or any other components not expressly authorized and approved by HHT; (8) modification of the appliance not expressly authorized and approved by HHT in writing; and/or (9) interruptions or fluctuations of electrical power supply to the applicable Product.
- Non-HHT venting components, hearth connections or other accessories used in conjunction with the applicable Product.
- Any part of a pre-existing fireplace system in which an insert or a decorative gas applicable Product is installed.
- HHT's obligation under this Warranty does not extend to the Product's capability to heat the desired space. Information is provided to assist the consumer and the dealer in selecting the proper Product for the application. Consideration must be given to the Product location and configuration, environmental conditions, insulation and air tightness of the structure.

### **This warranty is void if:**

- The applicable Product has been over-fired, operated in atmospheres contaminated by chlorine, fluorine, or other damaging chemicals. Over-firing can be identified by, but not limited to, warped plates or tubes, deformation/warping of interior cast iron structure or components, rust colored cast iron, bubbling, cracking and discoloration of steel or enamel finishes.
- The applicable Product is subjected to prolonged periods of dampness or condensation.
- There is any damage to the applicable Product due to water or weather damage which is the result of, but not limited to, improper chimney or venting installation.

### **LIMITATIONS OF REMEDIES AND LIABILITY:**

- **EXCEPT TO THE EXTENT PROVIDED BY LAW, HHT MAKES NO EXPRESS WARRANTIES OTHER THAN THE WARRANTY SPECIFIED HEREIN. The owner's exclusive remedy and HHT's sole obligation under this Warranty or in contract, tort or otherwise, shall be limited to replacement of the Component Part(s), repair of the Component Part(s), or refund of the original purchase price of the applicable Product(s), as specified above; provided, however, that (i) if HHT is unable to provide replacement of the Component Part(s) and repair of the Component Part(s) is not commercially practicable or cannot be timely made, or (ii) the customer is willing to accept a refund of the purchase price of the applicable Product(s), HHT may discharge all such obligations by refunding the purchase price of the applicable Product. In no event will HHT be liable for any incidental or consequential damages caused by defects in the applicable Product. Some States do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This Warranty gives you specific legal rights and you may also have other rights which vary from State to State. THE DURATION OF ANY IMPLIED WARRANTY IS LIMITED TO DURATION OF THE EXPRESSED WARRANTY SPECIFIED ABOVE FOR THE APPLICABLE PRODUCT. Some States do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you.**

## 2 Product Specific Information

### A. Appliance Certification

**MODELS:** QUARTZ32IFTN, QUARTZ32IFTL,  
QUARTZ36IFTN, QUARTZ36IFTL  
QUARTZ42IFTN, QUARTZ42IFTL  
**LABORATORY:** Underwriters Laboratories, Inc. (UL)  
**TYPE:** Direct Vent Heater  
**STANDARD:** CSA / ANSI Z21.88:19 • CSA 2.33:19

This product is listed to ANSI standards for “Vented Gas Fireplace Heaters” and applicable sections of “Gas Burning Heating Appliances for Manufactured Homes and Recreational Vehicles”, and “Gas Fired Appliances for Use at High Altitudes”. Also Certified for Installation in a Bedroom or a Bedsitting Room.

**NOTICE:** *This installation must conform with local codes. In the absence of local codes you must comply with the National Fuel Gas Code, ANSI Z223.1-latest edition in the U.S.A. and the CAN/CGA B149 Installation Codes in Canada.*

**NOT INTENDED FOR USE AS A PRIMARY HEAT SOURCE.**  
This appliance is tested and approved as either supplemental room heat or as a decorative appliance. It should not be factored as primary heat in residential heating calculations.

Installation and service of this appliance should be performed by qualified personnel. Hearth & Home Technologies recommends HHT Factory Trained or NFI certified professionals.



### B. Glass Specifications

Hearth & Home Technologies appliances manufactured with tempered glass may be installed in hazardous locations such as bathtub enclosures as defined by the Consumer Product Safety Commission (CPSC). The tempered glass has been tested and certified to the requirements of **ANSI Z97.1** and **CPSC 16 CFR 1202** (Safety Glazing Certification Council **SGCC# 1595** and **1597**. Architectural Testing, Inc. Reports **02-31919.01** and **02-31917.01**).

This statement is in compliance with **CPSC 16 CFR Section 1201.5** “Certification and labeling requirements” which refers to **15 U.S. Code (USC) 2063** stating “...Such certificate shall accompany the product or shall otherwise be furnished to any distributor or retailer to whom the product is delivered.”

Some local building codes require the use of tempered glass with permanent marking in such locations. Glass meeting this requirement is available from the factory. Please contact your dealer or distributor to order.

### C. BTU Specifications

| Models<br>(U.S. or Canada) |             | Maximum<br>Input BTU/h | Minimum<br>Input BTU/h | Orifice<br>Size<br>(DMS) |
|----------------------------|-------------|------------------------|------------------------|--------------------------|
| QUARTZ32IFTN<br>(NG)       | (0-2000 FT) | 21,000                 | 11,250                 | #44                      |
| QUARTZ32IFTL<br>(PROPANE)  | (0-2000 FT) | 18,500                 | 10,000                 | #55                      |
| QUARTZ36IFTN<br>(NG)       | (0-2000 FT) | 24,000                 | 13,000                 | #42                      |
| QUARTZ36IFTL<br>(PROPANE)  | (0-2000 FT) | 20,500                 | 11,500                 | #54                      |
| QUARTZ42IFTN<br>(NG)       | (0-2000 FT) | 28,500                 | 14,500                 | #39                      |
| QUARTZ42IFTL<br>(PROPANE)  | (0-2000 FT) | 26,000                 | 13,500                 | #53                      |

# 3 Important Safety and Operating Information

## A. Appliance Safety

**WARNING! DO NOT operate fireplace before reading and understanding operating instructions. Failure to operate fireplace according to operating instructions could cause fire or injury.**



**HOT GLASS WILL  
CAUSE BURNS.**

**DO NOT TOUCH GLASS  
UNTIL COOLED.**

**NEVER ALLOW CHILDREN  
TO TOUCH GLASS.**

- Keep children away.
- CAREFULLY SUPERVISE children in same room as fireplace.
- Children and adults should be alerted to the hazards of high surface temperatures and should stay away to avoid burns or clothing ignition.

**High temperatures may ignite clothing or other flammable materials.**

- Clothing, furniture, draperies, and other flammable materials must not be placed on or near the appliance.

**A barrier designed to reduce the risk of burns from the hot viewing glass is provided with this appliance and must be installed for the protection of children and other at-risk individuals. DO NOT operate the appliance with the barrier removed. If the barrier becomes damaged, the barrier must be replaced with the manufacturer's barrier for this appliance.**

Contact your dealer or Hearth & Home Technologies if the barrier is not present or help is needed to properly install one.

- Young children should be carefully supervised when they are in the same room as the appliance. Toddlers, young children and others may be susceptible to accidental contact burns.

A physical barrier is recommended if there are at risk individuals in the house. To restrict access to a fireplace or stove, install an adjustable safety gate to keep toddlers, young children and other at risk individuals out of the room and away from hot surfaces.

- Install a switch lock or a wall/remote control with child protection lockout feature.
- Keep remote controls out of reach of children.
- Never leave children alone near a hot fireplace, whether operating or cooling down.
- Teach children to NEVER touch the fireplace.

- Consider not using the fireplace when children will be present.

Contact your dealer for more information, or visit: [www.hpba.org/Product-Info/Fireplace-Stove-Heater/Glass-Fronts-Safety](http://www.hpba.org/Product-Info/Fireplace-Stove-Heater/Glass-Fronts-Safety).

To prevent unintended operation when not using your fireplace for an extended period of time (summer months, vacations, trips, etc):

- Remove batteries from remote controls.
- Turn off wall controls.
- Unplug 6 volt adapter plug (IPI) and remove batteries.
- Set the selector switch on the control module to the OFF position and remove batteries.




**WARNING:** This product and the fuels used to operate this product (liquid propane or natural gas), and the products of combustion of such fuels, can expose you to chemicals including benzene, which is known to the State of California to cause cancer and reproductive harm. For more information go to: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## Clear Space

**WARNING! DO NOT place combustible objects in front of the fireplace or block fireplace openings. High temperatures could start a fire. See Figure 3.1.**

Avoid placing candles and other heat-sensitive objects on mantel or hearth. Heat could damage these objects.



**Figure 3.1 Clear Space Requirement - All Models**

## B. General Operating Parts

Figure 3.2 references the general operating parts of the appliance and the section of this manual in which they are discussed.




Figure 3.2 General Operating Parts

## C. Fuel Specifications

**WARNING! Risk of Fire or Explosion!** Appliance must be set up for compatible gas type!

- This appliance is designed to operate on either natural gas or propane. Make sure the appliance is compatible with gas type selected for installation site.
- Conversions must be made by a qualified service technician using Hearth & Home Technologies specified and approved parts.

## D. Wall and Mantel Temperatures

### ANSI/CSA Standards

The American National Standards Institute (ANSI) and Canadian Standards Association (CSA) write the safety and performance standards to which all gas fireplaces are tested. The following are the allowable temperatures around and on a gas fireplace per the ANSI/CSA standards:

### Combustible Mantel and Surfaces around a Fireplace

The allowable temperature rise above ambient is 117°F for all exposed combustible surfaces around the fireplace, including the mantel, when installed according to the installation instructions. Non-combustible surfaces and mantels do not have a maximum temperature limit; however the installation instructions must still be followed for any restrictions on placement of non-combustible materials on or around the fireplace.

Example: The mantel above a fireplace in a room that is 70°F is allowed to reach but not exceed 187°F (70°F+117°F = 187°F).

## E. Good Faith Wall Surface/TV Guidelines





Figure 3.3 Good Faith Wall Surface Temperatures Above Appliance

**NOTICE:** Surface temperatures listed above are taken with a temperature measuring probe as prescribed by the test standard used for appliance certification. Temperatures on walls or mantels taken with an infrared thermometer may yield increased temperatures of up to 30 °F (17 °C) or more depending on the thermometer settings and material characteristics being measured. Use appropriate finishing materials that are able to withstand these conditions. For additional finishing guidelines, see Section 10 in the appliance installation manual.

# Good Faith Guidelines for TV Installations Above Appliance



- Notes:
- 1. These are good faith recommended clearances only and not a guarantee of compliance with all TV manufacturers’ maximum allowable operating temperatures.
  - 2. Since every home has unique air flow characteristics and maximum allowable operating temperatures can vary from manufacturer to manufacturer and from model to model, actual TV temperatures should be validated at the time of each installation. TVs should not be used in situations where the actual TV temperature exceeds the manufacturers’ maximum allowable operating temperatures identified in the TV’s technical specifications. Contact the TV’s manufacturer directly if you cannot locate this information or have questions regarding the information.
  - 3. Mantel height and depth must conform to mantle requirements specified in the appliance installation manual.
  - 4. “C” dimension taken from the top of the hood or appliance opening.
  - 5. Suggestions on how to further reduce TV temperatures:
    - a. Increase “A” dimension.
    - b. Increase “C” dimension, however, increasing “B” dimension beyond maximum recommended typically results in higher temperatures.

Figure 3.4 Good Faith TV Guidelines

## F. Before Lighting Appliance

Before operating this fireplace for the first time, **it is recommended that a qualified service technician:**

- Verify all shipping materials have been removed from inside and/or underneath the firebox.
- Review proper placement of logs, ember material and/or other decorative materials.
- Check the wiring.
- Check the air shutter adjustment.
- Ensure that there are no gas leaks.
- Ensure that the glass is sealed and in the proper position and that the integral barrier is in place.

***WARNING! Risk of Fire or Asphyxiation! DO NOT operate fireplace with fixed glass assembly removed.***

## G. Lighting Instructions (IPI)

### FOR YOUR SAFETY READ BEFORE LIGHTING




**WARNING:** If you do not follow these instructions exactly, a fire or explosion may result causing property damage, personal injury or loss of life.

- A. This appliance is equipped with an intermittent pilot ignition (IPI) device which automatically lights the burner. **DO NOT** try to light the burner by hand.
  - B. **BEFORE LIGHTING**, smell all around the appliance area for gas. Be sure to smell next to the floor because some gas is heavier than air and will settle on the floor.
- WHAT TO DO IF YOU SMELL GAS**
- **DO NOT** try to light any appliance.
  - **DO NOT** touch any electric switch; do not use any phone in your building.
  - Immediately call your gas supplier from a neighbor's phone. Follow the gas supplier's instructions.
  - If you cannot reach your gas supplier, call the fire department.
  - C. Use only your hand to push in or turn the gas control knob. Never use tools. If the knob will not push in or turn by hand, **DO NOT** try to repair it, call a qualified service technician. Force or attempted repair may result in a fire or explosion.
  - D. **DO NOT** use this appliance if any part has been under water. Immediately call a qualified service technician to inspect the appliance and to replace any part of the control system and any gas control which has been under water.

### LIGHTING INSTRUCTIONS (IPI)

1. This appliance is equipped with an ignition device which automatically lights the burner. **DO NOT** try to light the burner by hand.
2. Wait five (5) minutes to clear out any gas. Then smell for gas, including near the floor. If you smell gas, **STOP!** Follow "B" in the Safety Information located on the top of this label. If you do not smell gas, go to next step.
3. To light the burner:  
Equipped with wall switch: Turn ON/OFF switch to ON.  
Equipped with remote or wall control: Press ON or FLAME button.  
Equipped with thermostat: Set temperature to desired setting.
4. If the appliance does not light after three tries, call your service technician or gas supplier.

**GAS  
VALVE**



### TO TURN OFF GAS TO APPLIANCE

1. Equipped with wall switch: Turn ON/OFF switch to OFF.  
Equipped with remote or wall control: Press OFF button.  
Equipped with thermostat: Set temperature to lowest setting.
2. Service technician should turn off electric power to the control when performing service.



# DANGER



**HOT GLASS WILL CAUSE BURNS.**  
**DO NOT TOUCH GLASS UNTIL COOLED.**  
**NEVER ALLOW CHILDREN TO TOUCH GLASS.**

A barrier designed to reduce the risk of burns from the hot viewing glass is provided with this appliance and must be installed for the protection of children and other at-risk individuals.

## WARNING:

**DO NOT CONNECT LINE VOLTAGE (110/120 VAC OR 220/240 VAC) TO THE CONTROL VALVE.**

Improper installation, adjustment, alteration, service or maintenance can cause injury or property damage. Refer to the owner's information manual provided with this appliance. For assistance or additional information, consult a qualified installer, service agency or the gas supplier.

This appliance needs fresh air for safe operation and must be installed so there are provisions for adequate combustion and ventilation air.



**WARNING:** This product and the fuels used to operate this product (liquid propane or natural gas), and the products of combustion of such fuels, can expose you to chemicals including benzene, which is known to the State of California to cause cancer and reproductive harm. For more information go to: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Keep burner and control compartment clean. See installation and operating instructions accompanying appliance.

## CAUTION:

Hot while in operation. **DO NOT** touch. Keep children, clothing, furniture, gasoline and other liquids having flammable vapors away.

**DO NOT** operate the appliance with fixed glass assembly removed, cracked or broken. Replacement of the fixed glass assembly should be done by a licensed or qualified service person.

### NOT FOR USE WITH SOLID FUEL

For use with natural gas and propane. A conversion kit, as supplied by the manufacturer, shall be used to convert this appliance to the alternate fuel.

Also Certified for Installation in a Bedroom or a Bedsitting Room.

This appliance must be installed in accordance with local codes, if any; if none, follow the *National Fuel Gas Code, ANSI Z223.1/NFPA 54*, or the *National Gas and Propane Installation code, CSA B149.1*.

**For additional information on operating your  
Hearth & Home Technologies fireplace, please  
refer to [www.hearthnhome.com](http://www.hearthnhome.com).**

593-913K

## H. Appliance Break-In

**NOTICE! Open windows for air circulation during fireplace break-in.**

- Some people may be sensitive to smoke and odors.
- Smoke detectors may activate.

Follow the initial break-in procedure below to cure the materials used to manufacture the fireplace and the finishing materials around it.

- The fireplace should be run three to four hours continuously on high.
- Turn the fireplace off and allow it to cool completely.
- Remove fixed glass assembly. See Section 4.B.
- Clean fixed glass assembly. See Section 4.B.
- Replace the fixed glass assembly.

**Note:** Some installations may require additional run time to cure. If odors persist after the initial break-in period, run the fireplace for an additional three to four hours continuously on high.

**Note:** Some IPI systems have a safety feature that automatically shuts down the fireplace after 9 hours of continuous operation without receiving a command from the remote control. If this occurs, restart the appliance.

## I. Heat Management

### Heat Output

If an optional fan is installed, the fan speed is controlled by adjusting the speed control knob. Turn the knob clockwise to increase the fan speed and counterclockwise to decrease the fan speed.

### Burn Rate

These models have a variable burn rate which is controlled by the remote control. Therefore the flame height is adjustable.

The flame height may be adjusted as desired by locating the flame option on the remote control and adjusting up or down to desired flame height.

### Optional Heat Management Systems

An optional heat management system, which allows the heat from the appliance to be redirected as desired, may be installed with this appliance. It may be either a Heat-Zone®-Gas, which diverts heat into an adjacent room, and/or a HEAT-OUT-GAS which will divert heat outside the home/building.

Refer to Section 6 of the appliance installation manual to confirm which of the heat management systems may be installed together. All heat management systems must be installed by a qualified service technician at the time of appliance installation.

### Optional Heat-Zone®-Gas Kit

The HEAT-ZONE®-GAS heat management option is available for use with this appliance and must be used in conjunction with the IFT-RC400 control. The Heat-Zone Kit draws heat from your fireplace to an adjacent room in your home, up to 20 feet away.

### Optional Heat-Out-Gas Kit

The HEAT-OUT-GAS heat management option is available for use with this appliance and is operated with a wall switch. The Heat-Out-Gas kit draws heat from your fireplace and directs it outside, up to 25 feet away.

## J. Operation During A Power Outage - IntelliFire Touch®

The IntelliFire Touch intermittent pilot ignition system comes with a battery backup system that enables the system to operate in a power outage. The system offers seamless transition from household AC power to battery backup. A factory-installed battery pack is located in the control cavity of the appliance. See Figure 3.5. Battery longevity and performance will be affected by long term exposure to the service temperatures of this appliance.

**NOTICE:** Batteries should only be used as a power source in the event of an emergency power outage. Batteries should not be used as a primary long-term power source. Batteries tend to corrode over time.

### To Operate Fireplace Using Battery Power (DC):

1. Access the control cavity of the appliance. See Figure 3.5 for location. The decorative barrier front and front refractory may need to be removed.
2. Locate the battery tray and insert four AA cell batteries. Battery polarity must be correct or module damage will occur. See Figure 3.5. A complete wiring diagram is included in the Electrical section of the appliance Installation Manual.
3. Turn the appliance on according to the instructions below for the appropriate type of control:

Standard Wall Switch or Factory-Installed ON/OFF Switch:

- Toggle the switch as you would under normal circumstances.

Wireless Remote:

- Remote receiver is integrated into the ignition module
- Use the remote to turn the appliance on.
- To preserve battery life, do not use the HI/LO flame or THERMOSTAT options.

Ignition Module:

- Locate the ignition module in the control cavity.
- Slide the ON/REMOTE/OFF switch to the ON position.

**NOTICE:** Some functionality will be lost when using battery backup including fan, lights, or any other auxiliary functions that require household 110-120 VAC power.

### To Return to Operation Using Electrical (AC) Power

Standard Wall Switch or Factory-Installed ON/OFF Switch:

- Toggle the switch to OFF and remove the batteries from the battery tray. Replace door or decorative barrier front on appliance.


Wireless Remote:

- Slide the ON/REMOTE/OFF switch to the REMOTE position. Remove the batteries from the battery tray. Replace door or decorative barrier front on appliance.

Ignition Module:

- Slide the ON/REMOTE/OFF switch to the REMOTE position.

Remove the batteries from the battery tray. Replace door or decorative barrier front on appliance.



3.5 Battery Pack Located in Control Cavity

## K. Detailed Component Operating Instructions - IntelliFire Touch

### IFT-ECM Detailed Operating Instruction

The IFT-RC400 and IFT-RC150 remotes are an option for this model. The IntelliFire® Wi-Fi module (IFT-WFM) is also an option.

1. The Electronic Control Module (IFT-ECM) has a three-position ON/OFF/REMOTE selector switch that must be set for proper operation. See Figure 3.6. When changing switch positions, it is important to pause in each position for 1-2 seconds.

#### OFF Position:

The appliance will not respond to any commands from a wired wall switch, IFT-RC150 or IFT-RC400 remote controls. The unit should be in the OFF position during service, fuel conversion, and to reset the IFT-ECM in the event the system goes into a LOCK-OUT mode as the result of a system error. When switched to the OFF position while the appliance is operating, the system will shut down.

#### ON Position:

The appliance will ignite and run continuously at the HI flame setting. No adjustment in flame height is possible.

#### Remote Position:

The remote position allows operation of the appliance from a wired wall switch, IFT-RC400 or IFT-RC150 remote controls. The IFT-ECM switch must be in this position to pair the IFT-ECM with the IFT-ACM (if installed), and/or IFT-RC400 and IFT-RC150 remote controls. See the IFT-RC400 or IFT-RC150 installation manual for detailed instructions on pairing the IFT-ECM with the remote controls. After successfully pairing a IFT-RC400, all installed accessories can be controlled by the IFT-RC400 (see IFT-RC400 user manual). The RC150 allows the user to turn ON/OFF the flame in the appliance and activate the Cold Climate mode if desired. The IFT-ECM has a safety feature that will automatically shut down the fireplace after 9 hours of continuous operation without receiving a command from the IFT-RC400 or IFT-RC150.

**The IFT-ECM has a safety feature that will automatically shut down the fireplace after 9 hours of continuous operation in the ON position, except when operated in active thermostat mode.**

3. The Pilot button on the IFT-ECM activates the Cold Climate function of the fireplace. This function lights the pilot flame ONLY to provide enough heat in the firebox to reduce condensation in cool, high humidity ambient conditions. To activate the Cold Climate press and hold the Pilot button for one second and release. The IFT-ECM will flash two green LED blinks, beep twice and light and rectify the pilot flame when pressed to activate. To turn off Cold Climate, press and hold the Pilot button for one second and release. The IFT-ECM will flash one green LED blink, beep once and shut down the pilot flame. If remote controls are paired with the IFT-ECM, this feature can also be activated with the IFT-RC400 and/or IFT-RC150.




Figure 3.6 IFT-ECM



# DANGER



## Risk of Explosion

**DO NOT** cycle the ON/OFF/REM selector switch more than one time within a five minute period. Gas may accumulate in firebox. Call a qualified service technician.

4. An IFT-ECM reset is required if the module is in a lock-out condition. When this occurs, the appliance is shut down and the IFT-ECM status indicator LED will be blinking a RED/GREEN error code along with a one-time audible double-beep. If the IFT-ECM is in a lock-out condition, refer to the troubleshooting chart to interpret the error code and take corrective action as required. To reset the IFT-ECM after a lock-out error:

**CAUTION! Risk of burns!** Appliance surfaces are hot when operating and during cool down. Use care and wear gloves when opening the front and accessing components inside the appliance.

- Be aware the appliance may be HOT, use care in accessing the IFT-ECM.
- Set the IFT-ECM 3-position selector switch to OFF position.

- Wait five (5) minutes to allow possible accumulated gas to clear.
- Set the IFT-ECM 3-position selector switch to ON or REMOTE position. Module will beep once and flash a three GREEN LED code on successful startup.
- If placed in ON position, the appliance will ignite normally if the error condition was corrected.
- If placed in REMOTE position, use the paired IFT-RC400, IFT-RC150 or wired wall switch to start the appliance; appliance will ignite normally if the error condition was corrected.
- If the IFT-ECM re-enters the lock-out condition after these steps, call your dealer for service.

### **Appliance ON/OFF:**

A wall control, thermostat or remote control may be used to control the ON/OFF function of the appliance. Follow instructions included with the installed control.

### **Optional Fan Kit**

If desired, a fan kit may be added. Contact your dealer to order the correct fan kit.

### **Wi-Fi (Optional)**

If desired, a Wi-Fi module (IFT-WFM) may be added to allow the appliance to be run via an app. Contact your dealer to order.

# 4 Maintenance and Service

**IMPORTANT!** Any safety screen, decorative barrier front or guard removed for servicing must be replaced prior to operating the fireplace.

When properly maintained, your fireplace will give you many years of trouble-free service. **Contact your dealer** to answer questions regarding proper operation, trouble-shooting and service for your appliance. Visit [www.majesticproducts.com](http://www.majesticproducts.com) to locate a dealer. We recommend annual service by a qualified service technician.

## A. Maintenance: Frequency and Tasks

| Task                                  | Frequency  | To be completed by           |
|---------------------------------------|------------|------------------------------|
| Glass Cleaning                        | Seasonally | Homeowner                    |
| Surrounds, Decorative Barrier Fronts  | Annually   |                              |
| Remote Control                        | Seasonally |                              |
| Venting and Termination Cap           | Seasonally |                              |
|                                       |            |                              |
| Gasket Seal and Glass Inspection      | Annually   | Qualified Service Technician |
| Log Inspection                        | Annually   |                              |
| Firebox Inspection                    | Annually   |                              |
| Control Compartment & firebox Top     | Annually   |                              |
| Pilot and Burner Ignition & Operation | Annually   |                              |
| Electrical Service and Repair         | As needed  |                              |

## B. Maintenance Tasks - Homeowner

Installation and repair should be done by a qualified service technician only. The appliance should be inspected before use and at least annually by a professional service person.

The following tasks may be performed annually by the homeowner. If you are uncomfortable performing any of the listed tasks, please call your dealer for a service appointment.

More frequent cleaning may be required due to excessive lint from carpeting, bedding material, etc. It is imperative that control compartments, burners and circulating air passageways of the appliance be kept clean. Any safety screen, guard, or barrier removed for servicing the appliance must be replaced prior to operating the appliance.

**CAUTION! Risk of Burns!** The fireplace shall be turned off and cooled before servicing.

## Glass Cleaning

**Frequency:** Seasonally

**By:** Homeowner

**Tools Needed:** Protective gloves, gas fireplace glass cleaner, drop cloth and a stable work surface.

**CAUTION! Handle fixed glass assembly with care.** Glass is breakable.

- Avoid striking, scratching or slamming glass
- **DO NOT** use abrasive cleaners
- **DO NOT** clean glass while it is hot
- Prepare a work area large enough to accommodate fixed glass assembly and decorative barrier front by placing a drop cloth on a flat, stable surface.

**Note:** Fixed glass assembly and gasketing may have residue that can stain carpeting or floor surfaces.

- Remove decorative barrier front from fireplace and set aside on work surface.
- Clean glass with a non-abrasive, non-ammonia based, commercially available gas fireplace glass cleaner.
  - Light deposits: Use a soft cloth with soap and water
  - Heavy deposits: Use commercial fireplace glass cleaner (consult with your dealer)

## Removing Fixed Glass Assembly

- Remove decorative barrier front from fireplace and set aside on work area.
- Pull the four glass assembly latches out of the groove on the glass frame. Remove glass assembly from the appliance. See Figure 4.1.

## Replacing Fixed Glass Assembly

- Replace the glass assembly on the appliance. Pull out and latch the four glass assembly latches into the groove on the glass frame.




Figure 4.1 Fixed Glass Assembly

- Carefully set fixed glass assembly in place on fireplace. Hold glass in place with one hand and secure all glass latches with the other hand.
- Inspect and operate all glass latches to ensure they move freely and no obstructions are present.
- Reinstall decorative barrier front.

## **Surrounds, Decorative Barrier Fronts**

**Frequency:** Annually

**By:** Homeowner

**Tools needed:** Protective gloves, stable work surface

- Assess condition of screen and replace as necessary.
- Inspect for scratches, dents or other damage and repair as necessary.
- Check that air intake and discharge areas are not blocked.
- Vacuum and dust surfaces.

## **Remote Control**

**Frequency:** Seasonally

**By:** Homeowner

**Tools needed:** Replacement batteries and remote control instructions.

- Locate remote control transmitter and receiver.
- Verify operation of remote. Refer to remote control operation instructions for proper calibration and setup procedure.
- Replace batteries as needed in remote transmitters and battery-powered receivers.
- Place remote control out of reach of children.

If not using your fireplace for an extended period of time (summer months, vacations/trips, etc), to prevent unintended operation:

- Remove batteries from remote controls.
- Unplug 6 volt adapter plug on IPI models.

## **Venting and Termination Cap**

**Frequency:** Seasonally

**By:** Homeowner

**Tools needed:** Protective gloves and safety glasses.

- Inspect exposed venting and termination cap for blockage or obstruction such as plants, bird nests, leaves, snow, debris, etc.
- Verify termination cap clearance to subsequent construction (building additions, decks, fences, or sheds).
- Inspect for corrosion or separation.
- Verify caulking and sealing of vent components and termination cap remains intact.
- Inspect draft shield to verify it is not damaged or missing.

## C. Maintenance Tasks - Qualified Service Technician

The following tasks must be performed by a qualified service technician.

### Gasket Seal and Glass Assembly Inspection

**Frequency:** Annually

**By:** Qualified Service Technician

**Tools needed:** Protective gloves, drop cloth and a stable work surface.

- Inspect gasket seal and its condition.
- Inspect fixed glass assembly for scratches and nicks that can lead to breakage when exposed to heat.
- Confirm there is no damage to glass or glass frame. Replace as necessary.
- Verify that fixed glass assembly is properly retained and attachment components are intact and not damaged. Replace as necessary.

### Log Inspection

**Frequency:** Annually

**By:** Qualified Service Technician

**Tools needed:** Protective gloves.

- Inspect for damaged or missing logs. Replace as necessary. Refer to Installation manual for log placement instructions.
- Verify correct log placement and no flame impingement causing sooting. Correct as necessary.

### Firebox Inspection

**Frequency:** Annually

**By:** Qualified Service Technician

**Tools needed:** Protective gloves, sandpaper, steel wool, cloths, mineral spirits, primer and touch-up paint.

- Inspect for paint condition, warped surfaces, corrosion or perforation. Sand and repaint as necessary.
- Replace fireplace if firebox has been perforated.

### Control Compartment and Firebox Top

**Frequency:** Annually

**By:** Qualified Service Technician

**Tools needed:** Protective gloves, vacuum cleaner, dust cloths

- Vacuum and wipe out dust, cobwebs, debris or pet hair. Use caution when cleaning these areas. Screw tips that have penetrated the sheet metal are sharp and should be avoided.
- Remove all foreign objects.
- Verify unobstructed air circulation.

## Pilot and Burner Ignition and Operation

**Frequency:** Annually

**By:** Qualified Service Technician

**Tools needed:** Protective gloves, vacuum cleaner, whisk broom, flashlight, voltmeter, indexed drill bit set, and a manometer.

- Inspect orifice for soot, dirt and corrosion. Verify orifice size is correct. See Service Parts List for proper orifice sizing.
- Verify air shutter setting is correct. See Installation Manual for required air shutter setting. Verify air shutter is clear of dust and debris.
- Verify burner is properly secured and aligned with pilot or igniter.
- Clean off burner top, inspect for plugged ports, corrosion or deterioration. Replace burner if necessary.
- Inspect thermocouple/thermopile or IPI flame sensing rod for soot, corrosion and deterioration. Polish with 320 grit Emery cloth and/or 3M™ Scotch-Brite Abrasive Hand Pad.
- Verify that there is not a short in flame sense circuit by checking continuity between pilot hood and flame sensing rod. Replace pilot as necessary.
- Verify manifold and inlet pressures. Adjust regulator as required.
- Check all accessible gas-carrying tubes, connections, pipes and other components for leaks.
- Inspect pilot flame pattern and strength. See Figure 4.2 for proper pilot flame pattern. Clean or replace orifice spud as necessary.
- Replace Glowing embers with new dime-size pieces. **DO NOT** block ports or obstruct lighting paths. Refer to appliance installation manual for proper ember placement.
- Check for smooth lighting and ignition carryover to all ports. Verify that there is no ignition delay. Inspect and ensure the lighting of the main burner occurs within four seconds of the main gas valve opening.
- Inspect for lifting or other flame problems.
- Verify batteries have been removed from battery back-up IPI systems to prevent premature battery failure or leaking.



Figure 4.2 IPI Pilot Flame Patterns

## Electrical Service and Repair

**WARNING! Risk of Shock!** Label all wires prior to disconnection when servicing controls. Wiring errors could cause improper and dangerous operation. Verify proper operation after servicing.

**WARNING! Risk of Shock!** Replace damaged wire with type 105° C rated wire. Wire must have high temperature insulation.

# 5 Frequently Asked Questions and Troubleshooting

## A. Frequently Asked Questions - Appliance

| ISSUE                                                    | SOLUTIONS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|----------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Condensation on the glass                                | <p>This is a result of gas combustion and temperature variations. Prior to appliance being turned on, the inside of the glass has cooled below the dew point producing a byproduct of combustion: water in the form of condensation. As the fireplace glass warms, the condensation will disappear.</p> <p>In the summer, the inside of your fireplace contains hot humid air from outdoors. When the air from outdoors contacts glass cooled below the dew point by your air conditioning, moisture in that air will condense.</p> |
| Blue flames                                              | This is a result of normal operation and the flames will begin to yellow as the fireplace is allowed to burn for 20 to 40 minutes.                                                                                                                                                                                                                                                                                                                                                                                                  |
| Erratic flames                                           | <p>Verify that the glass assembly is correctly installed and that all glass latches are engaged over the tabs on the glass frame.</p> <p>Vent baffle/flue restrictor may be needed when long vertical vent runs are used. Refer to Installation Manual, Section 4 Vent Diagrams.</p>                                                                                                                                                                                                                                                |
| Odor from fireplace                                      | When first operated, this fireplace may release an odor for the first several hours. This is caused by the curing of the paint and the burning off of any oils remaining from manufacturing. Odor may also be released from finishing materials and adhesives used around the fireplace. These circumstances may require additional curing related to the installation environment.                                                                                                                                                 |
| Film on the glass                                        | This is a normal result of the curing process of the paint and logs. Glass should be cleaned within 3 to 4 hours of initial burning to remove deposits left by oils from the manufacturing process. A non-abrasive cleaner such as gas fireplace glass cleaner may be necessary. Contact your dealer.                                                                                                                                                                                                                               |
| Metallic noise                                           | Noise is caused by metal expanding and contracting as it heats up and cools down, similar to the sound produced by a furnace or heating duct. This noise does not affect the operation or longevity of the fireplace.                                                                                                                                                                                                                                                                                                               |
| Is it normal to see the pilot flame burn continually?    | In an intermittent pilot ignition system (IPI), the pilot flame should turn off when appliance is turned off. Some optional control systems available with IPI models may allow pilot flame to remain lit.                                                                                                                                                                                                                                                                                                                          |
| Optional Contemporary Kit (QUARTZ32IFT/QUARTZ36IFT only) | It is expected that some smaller pieces of rock may fall through small gaps around the burner/base pan and may result in a minor noise. This has no affect on fireplace performance and should lessen over time as the glass media becomes conditioned to the heating and cooling temperature changes.                                                                                                                                                                                                                              |
| Optional Glass Liner Kit                                 | It is normal for a white haze to accumulate on the reflective glass panels. Depending upon frequency of use, it is recommended that the glass panels are cleaned annually with a non-abrasive commercially available cleaner.                                                                                                                                                                                                                                                                                                       |
| Power Outages (battery backup)                           | This appliance can be operated on battery power in the event of a power outage. To access the battery pack, the decorative barrier front, mesh and glass assembly must be removed. Refer to Section 3 for more details.                                                                                                                                                                                                                                                                                                             |
| Wall above appliance feels hot to the touch.             | No action necessary. This appliance ships with a non-combustible material attached. Specifications of the attached non-combustible material are listed in the Installer's Manual for this appliance.                                                                                                                                                                                                                                                                                                                                |

**Contact your dealer** for additional information regarding operation and troubleshooting. Visit [www.majesticproducts.com](http://www.majesticproducts.com) to locate a dealer.

## B. Frequently Asked Questions - IntelliFire Touch Controls (Optional IFT-RC400)

| Symptom                                                                                                                   | Possible Cause                                                                                                                                        | Corrective Action                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| The appliance does not respond to commands from the remote control display does not light up when screen is touched.      | Batteries are depleted.                                                                                                                               | Verify batteries are new.                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|                                                                                                                           | Batteries are incorrectly oriented.                                                                                                                   | Verify batteries are installed in correct orientation as shown on batteries receptacle.                                                                                                                                                                                                                                                                                                                                                                                                              |
| The display on remote lights up when screen is touched but it does not respond to commands.                               | Touchscreen has lost calibration.                                                                                                                     | Touchscreen needs to be re-calibrated. Call dealer to have screen re-calibrated.                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                                                                                                           | Child Lock is ON.                                                                                                                                     | Check child lock icon located at the top of the remote display. If ON, it will show as a 'locked' symbol. To unlock, remove battery compartment door, locate child lock switch and move to 'unlock' position. Verify child lock icon on screen is now displayed in 'unlock' position.                                                                                                                                                                                                                |
| The remote displays the following message on-screen:<br>No dealer info available                                          | Dealer information not programmed into remote.                                                                                                        | Remote will still provide all available functions, and appliance is fully available for use. Call dealer to have them program.                                                                                                                                                                                                                                                                                                                                                                       |
| The remote displays the following message on-screen:<br>Call "Dealer Name & Number" to schedule maintenance.              | 300 hours of use. Appliance is still fully functional.                                                                                                | The appliance has been burning for 300 hours and is due for a regular maintenance. Call dealer to have them perform maintenance.                                                                                                                                                                                                                                                                                                                                                                     |
| The room temperature displayed on the remote is either slow or quick to respond while operating in thermostat mode.       | Remote is placed at a very short distance or too far away from the appliance.                                                                         | Try to keep the remote close to the appliance but not directly in front of it. The remote acts as the thermostat.                                                                                                                                                                                                                                                                                                                                                                                    |
|                                                                                                                           | Remote is placed in the path of an air draft or vent.                                                                                                 | Move the remote away from the direct path of air flow. The remote acts as the thermostat.                                                                                                                                                                                                                                                                                                                                                                                                            |
|                                                                                                                           | Flame Modulation                                                                                                                                      | The control system is designed to automatically adjust the flame intensity based on the difference between the desired room temperature, and actual temperature. In thermostat mode, the hearth appliance will start in HI flame, but as the actual temperature approaches the desired set temperature on the remote, the flame intensity will automatically decrease. Automatic flame modulation will result in more control of the temperature, and will cause the appliance to cycle OFF/ON less. |
| The appliance turns OFF the flame after extended periods of operation                                                     | 9 hour safety shutdown timer                                                                                                                          | This is normal behavior. The appliance has a safety timer that will automatically turn OFF the flame after nine hours of uninterrupted operation.                                                                                                                                                                                                                                                                                                                                                    |
| The remote displays the following message on-screen: Fan will turn on within 3 minutes                                    | Functioning as intended.                                                                                                                              | The appliance has a three minute delay timer before the fan is turned ON. This allows the air surrounding the appliance to be heated before being pushed into the room.                                                                                                                                                                                                                                                                                                                              |
| The remote displays the following message on-screen:<br>"Replace remote batteries."                                       | Low batteries in remote.                                                                                                                              | Install new batteries in the remote.                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| The remote is displaying an incorrect brand.                                                                              | Remote was programmed incorrectly.                                                                                                                    | Call dealer to have them program the remote with correct branding. Remote is still fully functional and the appliance is unaffected.                                                                                                                                                                                                                                                                                                                                                                 |
| After turning flame ON using remote, the flame does not turn ON immediately and instead a two minute timer is displayed.  | Power vent is installed on the appliance.                                                                                                             | This is expected behavior and the two minute timer is called a pre-purge timer. The flame will turn ON at the expiration of the timer.                                                                                                                                                                                                                                                                                                                                                               |
| The remote displays the following message on-screen:<br>"Remote Control Communication Error."                             | No power to appliance.                                                                                                                                | Verify home circuit breaker is on and master reset is on (if equipped).                                                                                                                                                                                                                                                                                                                                                                                                                              |
|                                                                                                                           | Power outage.                                                                                                                                         | Install new batteries in battery backup.                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| The remote displays the following message on -screen: Sorry your appliance did not start. Try again by pressing Flame On. | No power to appliance. No gas to appliance. Accumulation of air in gas line from extended period of appliance inactivity. Gas control system failure. | Verify that appliance has power and gas. Verify that the appliance accepts flame ON commands with an audible beep, and successfully turns flame on within 90 seconds. If this failure persists, contact dealer for service.                                                                                                                                                                                                                                                                          |

## C. Troubleshooting

With proper installation, operation, and maintenance your gas appliance will provide years of trouble-free service. If you do experience a problem, this troubleshooting guide will assist a qualified service technician in the diagnosis of a problem and the corrective action to be taken. This troubleshooting guide can only be used by a qualified service technician. Contact your dealer to arrange a service call by a qualified service technician.

### IntelliFire Touch

#### Error Codes:

| ECM LED Error Codes | Description                                                                                            |
|---------------------|--------------------------------------------------------------------------------------------------------|
| 3 Red: 1 Green      | IFT-RC400 error message: 'Appliance Safely Disabled', pilot sparks for 90 sec, no flame rectification. |
| 2 Red: 1 Green      | IFT-RC400 display: 'Error Pilot Flame', pilot valve solenoid not detected.                             |
| 2 Red: 2 Green      | Sparkling feedback signal error, spark coil failure.                                                   |
| 5 Red: 1 Green      | IFT-RC400 display: 'Error Power Vent' (if installed).                                                  |

See Troubleshooting matrix for more detail on Lock-out Error Codes, Possible Causes and Corrective Actions.

#### Troubleshooting:

| Symptom                                                                       | Possible Cause                                                                                                       | Corrective Action                                                                                                                                                                                                                                                                                                   |
|-------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pilot won't light, module clicks but no spark 90 sec, 3 Red/1 Green Lock out. | Incorrect wiring.                                                                                                    | Verify 'S' (White) sense wire and 'I' (orange) ignitor wire are connected to correct terminals on IFT-ECM.                                                                                                                                                                                                          |
|                                                                               | Loose connections or electrical shorts in wiring.                                                                    | Verify no loose connections or electrical shorts in wiring from module to pilot assembly. Verify wire insulation is not damaged. Verify wires are not grounding out to chassis, pilot burner, or any other metal object. Replace any damaged wires.                                                                 |
|                                                                               | Ignitor gap is too large.                                                                                            | Verify spark gap is approximately 0.095" (2.41 mm) to 0.135" (3.43 mm).                                                                                                                                                                                                                                             |
| Pilot won't light, there is no noise or spark.                                | No AC power, AC/DC adaptor faulty, backup batteries (if being used) depleted, IFT-ECM slider switch in OFF position. | Verify IFT-ECM slider switch is in ON or REM position. Verify AC power available to junction box. Verify AC/DC adaptor is plugged into junction box and ECM. Verify AC/DC adaptor output voltage is between 5.7-6.3 Vdc. If battery pack is used, check battery pack voltage is >4.2 V (if not, replace batteries). |
|                                                                               | Shorted or loose connection in system wiring or wiring harness.                                                      | Verify system wiring configuration. Remove and reinstall wiring harness that plugs into module. Check continuity of wires in valve wiring harness. Replace any damaged components.                                                                                                                                  |
|                                                                               | Poor or no system ground.                                                                                            | Verify black ground wire in valve harness is connected to metal chassis of fireplace.                                                                                                                                                                                                                               |
| Pilot won't light, there is no noise or spark, 2 Red/1 Green Lockout.         | Pilot solenoid not detected.                                                                                         | Check if valve harness orange wire is connected to pilot solenoid valve. Check pilot solenoid resistance, nominal is 40 ohms. If open or shorted, replace valve. Check valve harness wire continuity, if open replace 6-pin harness.                                                                                |
| Pilot won't light, there is no noise or spark, 2 Red/2 Green Lockout.         | Spark coil failure.                                                                                                  | Replace ECM.                                                                                                                                                                                                                                                                                                        |

## IntelliFire Touch - (continued)

| Symptom                                                                                                                         | Possible Cause                                          | Corrective Action                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pilot sparks but does not light, after 90 sec, 3 Red/1 Green Lockout                                                            | No gas supply.                                          | Verify incoming gas line ball valve is 'Open'. Verify inlet pressure is within requirement for gas type used. Contact gas supplier.                                                                                                                                                                                                                                                                                                                     |
|                                                                                                                                 | ECM has poor ground.                                    | Verify wiring, check valve harness black wire is securely grounded to metal chassis.                                                                                                                                                                                                                                                                                                                                                                    |
|                                                                                                                                 | Gas valve defective.                                    | Check pilot valve solenoid kick and hold voltages during ignition cycle. Kick V should be >1 V, hold V minimum 0.26 V. If voltages are OK, replace gas valve.                                                                                                                                                                                                                                                                                           |
| Pilot lights but main burner does not light. Pilot continues to spark for 90 sec then goes into 3 Red/1 Green Lockout.          | No flame detected. Flame rectification issue.           | Check if white sense lead is securely connected to 'S' terminal of IFT-ECM. Check resistance of sense lead between sense rod tip and connector to IFT-ECM, should be less than 1 ohm - if not, replace pilot assembly. Check system ground, ensure black valve harness wire is securely attached to metal chassis. Check wiring for damage. With system OFF, check resistance between tip of sense rod and pilot hood, should be resistance (>1 M-ohm). |
|                                                                                                                                 | No flame detected or sense rod contamination.           | With glass assembly installed, verify pilot flame is engulfing flame sense rod on pilot assembly. Verify inlet gas pressure is correct for gas type. Polish flame sense rod with fine steel wool to remove any contaminants that may have accumulated.                                                                                                                                                                                                  |
| Pilot lights and rectifies, but main burner does not light.                                                                     | Main valve solenoid.                                    | Check if green wire in valve harness is connected to green main valve solenoid. Check main valve solenoid resistance, nominal is 60 ohms. If open or shorted, replace valve. Verify valve inlet pressure is correct for gas type.                                                                                                                                                                                                                       |
| Pilot and main do not light, ECM goes into 5 Red/1 Green Lockout.                                                               | Power Vent (PV) Failure.                                | Power Vent blower defective - check wiring to IFT-ACM, check if blower is working. Check if PV pressure switch is connected to brown and black wire in 6-pin valve wire harness. Check if pressure switch is closed (shorted) when PV blower is running. Refer to PV troubleshooting instructions.                                                                                                                                                      |
| Appliance lights and runs for a few minutes then shuts down and/or appliance cycle ON and OFF with less than 90 sec of ON time. | Shorted or loose connection in flame detection circuit. | Check if white sense lead is securely connected to 'S' terminal of IFT-ECM. Check resistance of sense lead between sense rod tip and connector to IFT-ECM, should be less than 1 ohm - if not, replace pilot assembly. Check system ground, ensure black valve harness wire is securely attached to metal chassis. Check wiring for damage. With system OFF, check resistance between tip of sense rod and pilot hood, should be resistance (>1 M-ohm). |
|                                                                                                                                 | Poor flame rectification or contaminated sense rod.     | With glass assembly installed, verify pilot flame is engulfing flame sense rod on pilot assembly. Verify inlet gas pressure is correct for gas type. Polish flame sense rod with fine steel wool to remove any contaminants that may have accumulated. Verify no soot deposits are in sense rod to pilot hood gap.                                                                                                                                      |
|                                                                                                                                 | Logs are set up wrong.                                  | Remove and re-install logs per the log placement instructions.                                                                                                                                                                                                                                                                                                                                                                                          |
|                                                                                                                                 | Damaged pilot assembly.                                 | Verify the pilot assembly ceramic insulator around the flame sensing rod is not cracked, damaged or loose. Check resistance between tip of sense rod and IFT-ECM connector, should be less than 1 ohm. Replace pilot assembly if damage is detected.                                                                                                                                                                                                    |

# 6 Reference Materials

---

## A. Accessories

Install approved accessories per instructions included with accessories. Contact your dealer for a list of approved accessories.

***WARNING! Risk of Fire and Electric Shock! Use ONLY Hearth & Home Technologies-approved optional accessories with this appliance. Using non-listed accessories could result in a safety hazard and will void the warranty.***

## Remote Controls, Wall Controls and Wall Switches

After a qualified service technician has installed the remote control, wall control or wall switch, follow the instructions supplied with the control installed to operate your appliance:

For safety:

- Install a switch lock or a wall/remote control with child protection lockout feature.
- Keep remote controls out of reach of children.

Contact your dealer if you have questions.

## Optional IntelliFire Wi-Fi module with IntelliFire App

After a qualified service technician has installed the IntelliFire Wi-Fi module with the IntelliFire app, follow the instructions supplied to operate your appliance. Contact your dealer if you have questions.

## B. Service Parts




## Service Parts **QUARTZ32IFTN/QUARTZ32IFTL**

Quartz 32" Gas Fireplace - DV

Beginning Manufacturing Date: March 2020

Ending Manufacturing Date: Active

### Log Set Assembly



**IMPORTANT: THIS IS DATED INFORMATION.** Parts must be ordered from a dealer or distributor. **Hearth and Home Technologies does not sell directly to consumers.** Provide model number and serial number when requesting service parts from your dealer or distributor.



**Stocked  
at Depot**

| ITEM | DESCRIPTION            | COMMENTS | PART NUMBER        |   |
|------|------------------------|----------|--------------------|---|
|      | Log Set Assembly       |          | LOGS-QUARTZ32      | Y |
| 1    | Rear Left Base Log     |          | SRV2413-701        |   |
| 2    | Rear Right Base Log    |          | SRV2412-702        |   |
| 3    | Front Left Base Log    |          | SRV2413-703        |   |
| 4    | Front Right Base Log   |          | SRV2412-704        |   |
| 5    | Top Left Log           |          | SRV2413-705        |   |
| 6    | Middle Left Cross Log  |          | SRV2413-706        |   |
| 7    | Middle Right Cross Log |          | SRV2413-707        |   |
| 8    | Top Right Log          |          | SRV2413-708        |   |
| 9    | Drywall Support        |          | 2391-119           |   |
| 10   | Valve Assembly         |          | See following page |   |
| 11   | Burner Assembly        |          | 2412-007           | Y |
| 12   | Base Pan               |          | 2412-111           |   |
| 13   | Glass Door Assembly    |          | GLA-550TR          | Y |
| 14   | Hood                   |          | 2115-230           |   |
| 15   | Door                   |          | SRV2401-021        |   |
| 16   | Junction Box           |          | SRV4021-013        | Y |
| 17   | Elbow Heat Shield      |          | 385-290            |   |

Additional service part numbers appear on following page.

1/22




# Service Parts **QUARTZ36IFTN/QUARTZ36IFTL**

Quartz 36" Gas Fireplace - DV

Beginning Manufacturing Date: March 2020

Ending Manufacturing Date: Active

## Log Set Assembly



**IMPORTANT: THIS IS DATED INFORMATION.** Parts must be ordered from a dealer or distributor. **Hearth and Home Technologies does not sell directly to consumers.** Provide model number and serial number when requesting service parts from your dealer or distributor.



**Stocked  
at Depot**

| ITEM | DESCRIPTION            | COMMENTS | PART NUMBER        |   |
|------|------------------------|----------|--------------------|---|
|      | Log Set Assembly       |          | LOGS-QUARTZ36      | Y |
| 1    | Rear Left Base Log     |          | SRV2413-701        |   |
| 2    | Rear Right Base Log    |          | SRV2413-702        |   |
| 3    | Front Left Base Log    |          | SRV2413-703        |   |
| 4    | Front Right Base Log   |          | SRV2413-704        |   |
| 5    | Top Left Log           |          | SRV2413-705        |   |
| 6    | Middle Left Cross Log  |          | SRV2413-706        |   |
| 7    | Middle Right Cross Log |          | SRV2413-707        |   |
| 8    | Top Right Log          |          | SRV2413-708        |   |
| 9    | Drywall Support        |          | 2392-119           |   |
| 10   | Valve Assembly         |          | See following page |   |
| 11   | Burner Assembly        |          | 2413-007           | Y |
| 12   | Base Pan               |          | 2413-111           |   |
| 13   | Glass Door Assembly    |          | GLA-750TR          | Y |
| 14   | Hood                   |          | 2118-230           |   |
| 15   | Door                   |          | DBM36BK            |   |
| 16   | Junction Box           |          | SRV4021-013        | Y |
| 17   | Elbow Heat Shield      |          | 385-290            |   |

Additional service part numbers appear on following page.

1/22




# Service Parts **QUARTZ42IFTN/QUARTZ42IFTL**

Quartz 42" Gas Fireplace - DV

Beginning Manufacturing Date: March 2020

Ending Manufacturing Date: Active

## Log Set Assembly



**IMPORTANT: THIS IS DATED INFORMATION.** Parts must be ordered from a dealer or distributor. **Hearth and Home Technologies does not sell directly to consumers.** Provide model number and serial number when requesting service parts from your dealer or distributor.



**Stocked  
at Depot**

| ITEM | DESCRIPTION            | COMMENTS | PART NUMBER        |   |
|------|------------------------|----------|--------------------|---|
|      | Log Set Assembly       |          | LOGS-QUARTZ42      | Y |
| 1    | Rear Left Base Log     |          | SRV2414-709        |   |
| 2    | Rear Right Base Log    |          | SRV2414-710        |   |
| 3    | Front Left Base Log    |          | SRV2413-703        |   |
| 4    | Front Right Base Log   |          | SRV2414-711        |   |
| 5    | Top Left Log           |          | SRV2413-705        |   |
| 6    | Middle Left Cross Log  |          | SRV2413-706        |   |
| 7    | Middle Right Cross Log |          | SRV2413-707        |   |
| 8    | Top Right Log          |          | SRV2414-712        |   |
| 9    | Drywall Support        |          | 2393-119           |   |
| 10   | Valve Assembly         |          | See following page |   |
| 11   | Burner Assembly        |          | 2414-007           | Y |
| 12   | Base Pan               |          | 2414-111           |   |
| 13   | Glass Door Assembly    |          | GLA-950TR          | Y |
| 14   | Hood                   |          | 2121-230           |   |
| 15   | Door                   |          | DBM42BK            |   |
| 16   | Junction Box           |          | SRV4021-013        | Y |
| 17   | Elbow Heat Shield      |          | 385-290            |   |

Additional service part numbers appear on following page.


1/22



# QUARTZIFT

Beginning Manufacturing Date: March 2020  
Ending Manufacturing Date: Active

## #10 Valve Assembly



IMPORTANT: THIS IS DATED INFORMATION. Parts must be ordered from a dealer or distributor. **Hearth and Home Technologies does not sell directly to consumers.** Provide model number and serial number when requesting service parts from your dealer or distributor.



**Stocked  
at Depot**

| ITEM  | DESCRIPTION              | COMMENTS    | PART NUMBER |   |
|-------|--------------------------|-------------|-------------|---|
| 10.1  | Pilot Assembly NG        |             | 2106-169    | Y |
|       | Pilot Assembly Propane   |             | 2106-170    | Y |
|       | Pilot Tube               |             | SRV485-301  | Y |
| 10.2  | 3-Hole Grommet           |             | SRV2118-420 |   |
| 10.3  | Valve Bracket            |             | 2118-104    |   |
| 10.4  | Flex Ball Valve Assembly |             | SRV302-320  | Y |
| 10.5  | Valve NG                 |             | SRV2166-302 | Y |
|       | Valve Propane            |             | 2166-303    | Y |
| 10.6  | Male Connector           | Pkg of 5    | 303-315/5   |   |
| 10.7  | Jumper Wire              |             | SRV2187-198 | Y |
| 10.8  | Thermostat Wire Assembly |             | SRV2118-170 | Y |
| 10.9  | Battery Pack**           |             | SRV2326-134 | Y |
| 10.10 | Module, IFT Control      |             | SRV2326-130 | Y |
| 10.11 | Wire Harness, IFT 6 Pin  |             | SRV2326-132 | Y |
| 10.12 | Component Tray           |             | 2279-185    |   |
| 10.13 | 6 Volt Transformer       |             | SRV2326-131 | Y |
| 10.14 | Bulkhead w/Flex Tube     |             | SRV7000-156 | Y |
| 10.15 | Shutter Bracket Assembly |             | 2118-121    |   |
|       | Orifice NG (#44C)        | QUARTZ32IFT | 582-844     | Y |
|       | Orifice Propane (#55C)   |             | 582-855     | Y |
|       | Orifice NG (#42C)        | QUARTZ36IFT | 582-842     | Y |
|       | Orifice Propane (#54C)   |             | SRV582-854  | Y |
|       | Orifice NG (#39C)        | QUARTZ42IFT | 582-839     | Y |
|       | Orifice Propane (#53C)   |             | 582-853     | Y |

\*\*Fuse for battery pack can be sourced locally, not a warranty item. Specs are 250v, 3A fuse, 3/4" long

Additional service part numbers appear on following page.

# QUARTZIFT

Beginning Manufacturing Date: March 2020  
Ending Manufacturing Date: Active

**IMPORTANT: THIS IS DATED INFORMATION.** Parts must be ordered from a dealer or distributor. **Hearth and Home Technologies does not sell directly to consumers.** Provide model number and serial number when requesting service parts from your dealer or distributor.



## Stocked at Depot

| ITEM            | DESCRIPTION                                                                                    | COMMENTS  | PART NUMBER   |   |
|-----------------|------------------------------------------------------------------------------------------------|-----------|---------------|---|
|                 | Exhaust Restrictor                                                                             |           | 530-299       |   |
|                 | Gasket Assembly                                                                                |           | 2118-080      |   |
|                 | Contains Burner neck, shutter bracket, vent, seal cap, valve plate,<br>and air passage gaskets |           |               |   |
|                 | Mineral Wool                                                                                   |           | 050-721       |   |
|                 | Touch Up Paint                                                                                 |           | TUP-GBK-12    |   |
|                 | Shoulder Bolt                                                                                  | Pkg of 25 | 319-835-25    |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
|                 |                                                                                                |           |               |   |
| CONVERSION KITS |                                                                                                |           |               |   |
|                 | Conversion Kit NG                                                                              |           | NGKQUARTZ-IFT |   |
|                 | Conversion Kit Propane                                                                         |           | LPKQUARTZ-IFT |   |
|                 | Pilot Orifice NG                                                                               |           | SRV593-528    | Y |
|                 | Pilot Orifice Propane                                                                          |           | SRV593-527    | Y |
|                 | Regulator NG                                                                                   |           | NGK-DXV-50    | Y |
|                 | Regulator Propane                                                                              |           | SRVLPK-DXV-50 | Y |

C. Contact Information



Majestic, a brand of Hearth & Home Technologies  
7571 215<sup>th</sup> Street West, Lakeville, MN 55044  
[www.majesticproducts.com](http://www.majesticproducts.com)

Please contact your Majestic dealer with any questions or concerns.  
For the location of your nearest Majestic dealer,  
please visit [www.majesticproducts.com](http://www.majesticproducts.com).

- NOTES -

---

---

---

---

---

---

---

---

---

---

|                                                                                                              |                                                                                                                                       |                                                                                                                   |
|--------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| <b>NOTICE</b>                                                                                                |                                                                                                                                       |                                                                                                                   |
|                           | <b>DO NOT DISCARD THIS MANUAL</b>                                                                                                     |                              |
| <ul style="list-style-type: none"><li>• Important operating and maintenance instructions included.</li></ul> | <ul style="list-style-type: none"><li>• Read, understand and follow these instructions for safe installation and operation.</li></ul> | <ul style="list-style-type: none"><li>• Leave this manual with party responsible for use and operation.</li></ul> |

This product may be covered by one or more of the following patents: (United States) 6601579, 6769426, 6863064, 7077122, 7074035, 7098269, 7234932, 7258116, 7322819, 7422011, 7470729, 7726300, 8147240, 9625149 or other U.S. and foreign patents pending.

2000-945E

Printed in U.S.A. - Copyright 2022